

Please download PDF and fill in the boxes. Use 'Additional Information' for non standard requests. Return form to sales@thermal-detection.com or fax to +44 1642 618307

Name: _____ Email: _____
 Organisation: _____ Tel: _____
 Country _____

Section 1 - unit dimensions in mm, select options required

Pocket Diameter _____

Pocket immersion Length in mm (if screw or flanged connection specified, this is the length below screw or flange) _____

Terminal Head Material _____

Section 2 - Insert Sensor Configuration Sensor Number Single Duplex Triplex	Thermocouple Type T Hot Junction G Grounded s Insulated	PT100 PT1000 Class A Tolerance Wires Class 'A' 2 wire Class 'AA' 3 wire 1/10 DIN 4 wire
---	---	--

Section 3 Process Connections None Fixed Thread → + Adjustable Compression Fitting Flange (specify) _____	Termination Options DIN plate Ceramic Block Transmitter - In Head Transmitter - DIN rail Transmitter Range Min/Max °C /	Optional Extras 3.1 Material Certs for wetted parts ADIF Statement <0.8RA Surface Finish Electropolishing UKAS Calibration indicate temperature points
--	---	---

Section 4 - Application Details Number of probes required _____ Industry Type _____	Additional information _____
--	------------------------------