

Please download PDF and fill in the boxes. Use 'Additional Information' for non standard requests.
Return form to sales@thermal-detection.com or fax to +44 1642 618307

Name: _____ Email: _____
 Organisation: _____ Tel: _____
 Country _____

Section 1 - unit dimensions in mm, select options required		Head Selection
Service Temperature Range (min/max °C) PT100 500 °C max T/C 850 °C max / Probe Material	Probe Diameter Probe Length	

Section 2 - Sensor Configuration	Thermocouple Only <table style="width:100%;"> <tr> <th>Hot Junction</th> <th>Type</th> </tr> <tr> <td>G Grounded</td> <td>Type 'T'</td> </tr> <tr> <td>s Insulated</td> <td>Type 'K'</td> </tr> <tr> <td></td> <td>Type 'J'</td> </tr> <tr> <td></td> <td>Type 'E'</td> </tr> </table>	Hot Junction	Type	G Grounded	Type 'T'	s Insulated	Type 'K'		Type 'J'		Type 'E'	PT100 Only <table style="width:100%;"> <tr> <th>Type</th> <th>Wires</th> </tr> <tr> <td>Class 'B'</td> <td>2 wire</td> </tr> <tr> <td>Class 'A'</td> <td>3 wire</td> </tr> <tr> <td>1/3 DIN</td> <td>4 wire</td> </tr> <tr> <td>1/10 DIN</td> <td></td> </tr> </table>	Type	Wires	Class 'B'	2 wire	Class 'A'	3 wire	1/3 DIN	4 wire	1/10 DIN	
Hot Junction	Type																					
G Grounded	Type 'T'																					
s Insulated	Type 'K'																					
	Type 'J'																					
	Type 'E'																					
Type	Wires																					
Class 'B'	2 wire																					
Class 'A'	3 wire																					
1/3 DIN	4 wire																					
1/10 DIN																						
Sensor Number Single Duplex Triplex																						

Section 3 Reduced Probe Tip	Process Connections	In head Transmitters
	None Fixed Thread Compression → + Flanged Hygienic	Transmitter Type Transmitter Range Min/Max °C /

Section 4 - Application Details	
Number of probes required	Additional information
Industry Type	

Available Heads

Form B



KNE



BUZ (Aluminium or st st)



BUZ-H Duplex



KPP White FDA



YCE



KSE mini



LS 316 stst



MA mini

